

Shower toilet, rimless, wall-hung with seat and cover 82060.1 ... 000 1



TECHNICAL DATA

Order no.	82060.1 ... 000 1
Certified to	CE, IPX4, EN 13077, SVGW Drinking water standards EN 1717
matching for	LIS CW2 Concealed frame with cistern for shower toilets, order no. 89466.1, 89466.6
Specifications	Shower toilet, rimless, wall-hung, with ceramic surface refinement LCC (only white) Washdown, flushing from 6 l to 4.5 l Concealed fixation Rotary button for shower function
Functions	Rear shower and lady shower adjustable in pressure & position Oscillation function Temperature adjustable via mobile app (ios/Android) Self cleaning of shower head before and after every use Exchangeable shower head is fully recessed in the ceramic with a cover ring LED signal light Integrated descaling function
Water pressure & temperature	Shower 7 pressure levels Flow rate ca. 3.5 l/min Temperature level via mobile app (ios/Android)
Water inlet	concealed, G 3/8" Water flow pressure range 0.1 to 1 MPa (1-10 bar) Operating temperature range +5 to +40 °C
Outlet	DN 90 mm horizontal
WC seat and cover	included Duroplast, removable, with lowering system, order no. 89160.1

Power supply & consumption	concealed Rated voltage 220 to 230 V, 50/60 Hz Direct connection by NYM cable possible External connection with Laufen cable routing possible, order no. 89560.3 (to be ordered separately) Power consumption in use max. 1'150 W Protection rating IPX4 Protection class I
Weight	33,0 kg
Accessories incl.	Rotary button for shower function
Mounting acc. incl.	Inlet and outlet pipes, fastening kit M12 with connection plate, incl. mounting tool, sound insulation set (DIN 4109) and water connection set for shower toilet
Mounting acc. excl.	External cable routing, order no. 89560.3 Stone screw fastening kit M12
Colours	400 – White LCC, 757 – White matt

SPECIFICATION TEXT

Shower toilet, rimless, wall-hung, washdown Laufen CLEANET NAVIA toilet pan sanitary ceramic, with ceramic surface refinement LCC (only white)

WC seat and cover Duroplast, removable, with lowering system CE, IPX4, EN 13077, SVGW, Drinking water standards EN 1717 min. 4.5/3-l-flush, dimensions 370 x 580 x 380 mm, concealed fixation

Special feature: Rear shower and lady shower, with adjustable water pressure and position, temperature adjustable via mobile app (ios/Android), oscillation function, integrated self cleaning shower head before and after every use, LED signal light, concealed water supply and power supply

Order no. 82060.1 ... 000 1

TECHNICAL DRAWINGS / S 1 : 20

